

CHCN*AV*

Make your work more efficient

Model •

i80

Surveying & Engineering Features:

- Lightweight - only 1.22kg with battery
- 220 Multi-constellation Receiver
- Sunlight readable LCD
- TILT compensation E bubble
- Internal TRx UHF
- Built-in Bluetooth & WiFi
- 32Gb internal memory
- Can be used without a data recorder
- Hot swappable batteries
- 3.75G network modem
- Field tested in Australia

Australia's Fully Featured RTK GPS Solution

Base &/or Rover System



Cast Magnesium Housing

GPS • GLONASS • Galileo • BeiDou • QZSS • SBAS

Software

Choose **Carlson SurvCE-GPS**
OR
Carlson SurvPC-GPS (larger screens)
OR
Field Genius-GPS
OR
LandStar (Android)



Ask about our special CORS ready
Rover Package



Convenient
hot swappable
batteries



Rover kit in waterproof field case

SUPPORTED THROUGHOUT AUSTRALIA

GNSS Characteristics

- 220 channels with all in view simultaneously tracked satellite signals
 - GPS: L1C/A, L2C, L2E, L5
 - GLONASS: L1C/A, L1P, L2C/A, L2P, L3
 - Galileo: E1, E5A, E5B
 - BDS: B1, B2
 - SBAS: L1C/A, L5 (QZSS, WAAS, EGNOS, GAGAN)

GNSS Accuracies ⁽¹⁾

- Real Time Kinematic (RTK):
 - Horizontal: 8 mm + 1 ppm RMS
 - Vertical: 15 mm + 1 ppm RMS
 - Initialization Time: < 5 s
 - Initialization Reliability: > 99.9%
- Network RTK:
 - Horizontal: 8 mm + 0.5 ppm RMS
 - Vertical: 15 mm + 0.5 ppm RMS
 - Initialization Time: < 10 s
 - Initialization Reliability: > 99.9%
- Post-processed Kinematic (PPK):
 - Horizontal: 8 mm + 1 ppm RMS
 - Vertical: 15 mm + 1 ppm RMS
- High-precision Static:
 - Horizontal: 2.5 mm + 0.1 ppm RMS
 - Vertical: 3.5 mm + 0.4 ppm RMS
 - Baseline Length: 300km
- SBAS: 0.5 m RMS

Hardware

- Size (H x W): 14 cm x 12.4 cm (5.5 in x 4.9 in)
- Weight: 1.02 kg (2.2 lb)
1.22 kg (2.7 lb) with batteries
- Environment:
 - Operating: -40°C to +75°C (-40°F to +167°F)
 - Storage: -55°C to +85°C (-67°F to +185°F)
- Humidity: 100% condensation
- Dust and Water Proof: IP67
- Shock and Vibration: 2 m (6.56 ft) fall onto concrete
- LCD: 128 x 64 dpi sunlight readable with function/accept buttons

Certifications and Calibrations

- FCC Part 15 (class B Device), FCC Part 22, 24, 90; CE Mark; C-Tick; Bluetooth EPL; IGS & NGS Antenna Calibration; MIL-STD-810G.



"We own three i80 CHC GNSS units and use Archer 2 hand controllers with SurvCE software and the ease of use and virtually an instant Fix plus the ability to continue work under dense trees and close to buildings, outperforms our other brands of RTK GPS. I highly recommend any surveyor to purchase the i80."

MICK FRIEDMAN
Surveyor, Gold Coast QLD 2017

Communications and Data Recording

- Serial: 2 x 7-pin LEMO port (external power, USB data download, USB update, RS-232)
- Network Modem: Internally integrated 3.75G modem
 - HSPA+ 21 Mbps (download), 5.76 Mbps (upload)
 - WCDMA 850/900/1700/1900/2100
 - EDGE/GPRS/GSM 850/900/1800/1900
- Bluetooth®: Internally integrated multimode system compatible with Android, Windows Mobile and Windows desktop operating systems
- Wi-Fi: 802.11 b/g/n, access point mode
- UHF Radios⁽²⁾: Protected TNC Female
 - Standard Internal Rx/Tx: 410 MHz to 470 MHz
 - Transmit power: 0.5 W to 2 W
 - Protocol: CHC, Trimble, Pacific Crest
 - Range: 5 km optimal conditions
 - FCC Certified Internal Rx/Tx: 403 MHz to 473 MHz
 - Transmit power: 0.1 W to 1 W
 - Protocols Trimble, Satel, Pacific Crest
 - Range: 5 km optimal conditions
- Protocols:
 - CMR, CMR+, SCMRX input and output
 - RTCM 2.x, RTCM 3.x input and output
 - NMEA 0183 output
 - HCN, HRC and RINEX static formats
 - NTRIP Client, NTRIP Caster
- Data Storage
 - 32 GB high-speed memory

Electrical

- Power Consumption: 3.2 W (depending on user settings)
- Li-ion Battery Capacity: 2 x 3400 mAh, 7.4 V
- Operating Time⁽³⁾:
 - RTK UHF Base: 6 h
 - RTK Rover: 10 h
 - Static: 12 h
- External Power: 12 V DC to 36 V DC

ROVER PACKAGE

Receive **20% off** your first year's
CORS Network subscription
Plus a **FREE** 2m Carbon GPS Pole

FINANCE PACKAGES: CHC GPS

- No Financials under \$55k
- Easy monthly payments from 2 years to 5 year terms
- Own the equipment at end of the term
- Bundle other items with GPS

Fast Replacement

Next day* delivery under warranty for rover or base.

*TNT Air Overnight

i80 RTK GPS

**Data Controllers - You Choose:
Use your own* or pick one of ours**



www.junipersys.com

*must be compatible with SurvCE

DL6 NEW GENERATION DATA LINK



- Six adjustable transmit power option from 5W to 28W
- Supports multiple protocols
- Rugged design
- Easy & quick set-up

General Specification

- Communication:
 - 1 x RS232 serial port, up to 115200 bps
- User interface: 1 digital display, 3 button, 4 status indicator

Power

- External Power: 9 V DC to 16 V DC

Modem Specifications

- Link Rate
 - 4800 bps
 - 9600 bps
 - 19200 bps
- Modulation: GMSK
- Link Protocol: CHC, Transparent, TT450S

Radio Specifications

- Frequency Bands: 410 MHz to 470 MHz
- Transmit Power
 - Low: 5 W/10 W/15 W
 - High: 20 W/25 W/28 W
- Type Certification: FCC, CE

Physical

- Size (L x W x H): 180 mm x 140 mm x 6.50 mm (7.1 in x 5.5 in x 2.6 in)
- Weight: 1.5 kg (52.9 oz)
- Environment
 - Operating: -30°C to +65°C (-22 °F to +149°F)
 - Storage: -55°C to +75°C (-67 °F to +167°F)
- Dust and Water Proof: IP67
- Serial: 1 x 5-pin LEMO port (external power, RS-232)
- Mount: Tripod bracket

Antenna

- External: 50 Ohm, TNC female connector

Australian Authorised Reseller



**AUSTRALIAN
DISTRIBUTOR**

Reg Offices & Training: Level 2, 139 Frome St, Adelaide, South Australia 5000

Delivery: 17 Jellicoe St, Linden Park, South Australia 5065

Mobile **0408 688 826**

sales@UAS-Australia.com.au www.UAS-Australia.com.au